

# util-vserver (libvserver) Reference Manual

## 0.30.212

Generated by Doxygen 1.5.2

Fri Apr 20 12:41:22 2007

## Contents

<a href="#">1</a>	<a href="#">util-vserver (libvserver) Module Index</a>	<a href="#">1</a>
<a href="#">2</a>	<a href="#">util-vserver (libvserver) Data Structure Index</a>	<a href="#">1</a>
<a href="#">3</a>	<a href="#">util-vserver (libvserver) File Index</a>	<a href="#">2</a>
<a href="#">4</a>	<a href="#">util-vserver (libvserver) Module Documentation</a>	<a href="#">2</a>
<a href="#">5</a>	<a href="#">util-vserver (libvserver) Data Structure Documentation</a>	<a href="#">10</a>
<a href="#">6</a>	<a href="#">util-vserver (libvserver) File Documentation</a>	<a href="#">18</a>

## 1 util-vserver (libvserver) Module Index

### 1.1 util-vserver (libvserver) Modules

Here is a list of all modules:

<a href="#">Syscall wrappers</a>	<a href="#">2</a>
<a href="#">Helper functions</a>	<a href="#">8</a>

## 2 util-vserver (libvserver) Data Structure Index

### 2.1 util-vserver (libvserver) Data Structures

Here are the data structures with brief descriptions:

<a href="#">Mapping_uint32</a>	<a href="#">10</a>
<a href="#">Mapping_uint64</a>	<a href="#">11</a>
<a href="#">vc_ctx_caps (Capabilities of process-contexts )</a>	<a href="#">11</a>
<a href="#">vc_ctx_dlimit</a>	<a href="#">12</a>
<a href="#">vc_ctx_flags (Flags of process-contexts )</a>	<a href="#">12</a>
<a href="#">vc_ctx_stat (Statistics about a context )</a>	<a href="#">12</a>
<a href="#">vc_err_listparser (Information about parsing errors )</a>	<a href="#">13</a>
<a href="#">vc_ip_mask_pair</a>	<a href="#">13</a>
<a href="#">vc_net_caps</a>	<a href="#">14</a>
<a href="#">vc_net_flags</a>	<a href="#">14</a>

<a href="#">vc_net_nx</a>	14
<a href="#">vc_nx_info</a>	15
<a href="#">vc_rlimit</a> (The limits of a resources )	15
<a href="#">vc_rlimit_mask</a> (Masks describing the supported limits )	16
<a href="#">vc_rlimit_stat</a> (Statistics for a resource limit )	16
<a href="#">vc_set_sched</a>	17
<a href="#">vc_virt_stat</a> (Contains further statistics about a context )	17
<a href="#">vc_vx_info</a>	18

## 3 util-vserver (libvserver) File Index

### 3.1 util-vserver (libvserver) File List

Here is a list of all documented files with brief descriptions:

<a href="#">internal.h</a> (Declarations which are used by util-vserver internally )	18
<a href="#">vserver.h</a> (The public interface of the the libvserver library )	19

## 4 util-vserver (libvserver) Module Documentation

### 4.1 Syscall wrappers

#### Functions

- [int vc\\_syscall](#) (uint32\_t cmd, [xid\\_t](#) xid, void \*data)  
*The generic vserver syscall.*
- [int vc\\_get\\_version](#) ()  
*Returns the version of the current kernel API.*
- [int vc\\_get\\_vci](#) ()  
*Returns the kernel configuration bits.*
- [xid\\_t vc\\_new\\_s\\_context](#) ([xid\\_t](#) ctx, unsigned int remove\_cap, unsigned int flags)  
*Moves current process into a context.*
- [int vc\\_set\\_ipv4root](#) (uint32\_t bcast, size\_t nb, struct [vc\\_ip\\_mask\\_pair](#) const \*ips)  
*Sets the ipv4root information.*
- [xid\\_t vc\\_ctx\\_create](#) ([xid\\_t](#) xid)  
*Creates a context without starting it.*

- `int vc_ctx_migrate (xid_t xid)`  
*Moves the current process into the specified context.*
- `int vc_ctx_stat (xid_t xid, struct vc_ctx_stat *stat)`  
*Get some statistics about a context.*
- `int vc_virt_stat (xid_t xid, struct vc_virt_stat *stat)`  
*Get more statistics about a context.*
- `int vc_get_rlimit (xid_t xid, int resource, struct vc_rlimit *lim)`  
*Returns the limits of resource.*
- `int vc_set_rlimit (xid_t xid, int resource, struct vc_rlimit const *lim)`  
*Sets the limits of resource.*
- `int vc_rlimit_stat (xid_t xid, int resource, struct vc_rlimit_stat *stat)`  
*Returns the current stats of resource.*
- `int vc_reset_minmax (xid_t xid)`  
*Resets the minimum and maximum observed values for all resources.*
- `int vc_ctx_kill (xid_t ctx, pid_t pid, int sig)`  
*Sends a signal to a context/pid.*
- `int vc_get_iattr (char const *filename, xid_t *xid, uint_least32_t *flags, uint_least32_t *mask)`  
*Returns information about attributes and assigned context of a file.*
- `xid_t vc_get_task_xid (pid_t pid)`  
*Returns the context of the given process.*
- `xid_t vc_getfilecontext (char const *filename)`  
*Returns the context of filename.*
- `int vc_wait_exit (xid_t xid)`  
*Waits for the end of a context.*

#### 4.1.1 Detailed Description

Functions which are calling the vserver syscall directly.

#### 4.1.2 Function Documentation

##### 4.1.2.1 `xid_t vc_ctx_create (xid_t xid)`

Creates a context without starting it.

This functions initializes a new context. When already in a freshly created context, this old context will be discarded.

**Parameters:**

*xid* The new context; special values are:

- VC\_DYNAMIC\_XID which means to create a dynamic context

**Returns:**

the xid of the created context, or VC\_NOCTX on errors. `errno` will be set appropriately.

**4.1.2.2 int vc\_ctx\_kill (xid\_t ctx, pid\_t pid, int sig)**

Sends a signal to a context/pid.

Special values for *pid* are:

- -1 which means every process in ctx except the init-process
- 0 which means every process in ctx inclusive the init-process

**4.1.2.3 int vc\_ctx\_migrate (xid\_t xid)**

Moves the current process into the specified context.

**Parameters:**

*xid* The new context

**Returns:**

0 on success, -1 on errors

**4.1.2.4 int vc\_ctx\_stat (xid\_t xid, struct vc\_ctx\_stat \* stat)**

Get some statistics about a context.

**Parameters:**

*xid* The context to get stats about

*stat* Where to store the result

**Returns:**

0 on success, -1 on errors.

**4.1.2.5 int vc\_get\_iattr (char const \* filename, xid\_t \* xid, uint\_least32\_t \* flags, uint\_least32\_t \* mask)**

Returns information about attributes and assigned context of a file.

This function returns the VC\_IATTR\_XXX flags and about the assigned context of a file. To request an information, the appropriate bit in *mask* must be set and the corresponding parameter (*xid* or *flags*) must not be NULL.

E.g. to receive the assigned context, the VC\_IATTR\_XID bit must be set in *mask*, and *xid* must point to valid memory.

Possible flags are VC\_IATTR\_ADMIN, VC\_IATTR\_WATCH, VC\_IATTR\_HIDE, VC\_IATTR\_BARRIER, VC\_IATTR\_IUNLINK and VC\_IATTR\_IMMUTABLE.

**Parameters:**

*filename* The name of the file whose attributes shall be determined.

*xid* When non-zero and the VC\_IATTR\_XID bit is set in *mask*, the assigned context of *filename* will be stored there.

*flags* When non-zero, a bitmask of current attributes will be stored there. These attributes must be requested explicitly by setting the appropriate bit in *mask*

*mask* Points to a bitmask which tells which attributes shall be determined. On return, it will masquerade the attributes which were determined.

**Precondition:**

```
mask!=0 && !((*mask&VC_IATTR_XID) && xid==0) && !((*mask&~VC_IATTR_XID) && flags==0)
```

**4.1.2.6 int vc\_get\_rlimit (xid\_t xid, int resource, struct vc\_rlimit \* lim)**

Returns the limits of *resource*.

**Parameters:**

*xid* The id of the context

*resource* The resource which will be queried

*lim* The result which will be filled with the limits

**Returns:**

0 on success, and -1 on errors.

**4.1.2.7 xid\_t vc\_get\_task\_xid (pid\_t pid)**

Returns the context of the given process.

**Parameters:**

*pid* the process-id whose xid shall be determined; pid==0 means the current process.

**Returns:**

the xid of process *pid* or -1 on errors

**4.1.2.8 int vc\_get\_vci ()**

Returns the kernel configuration bits.

**Returns:**

The kernel configuration bits

**4.1.2.9 int vc\_get\_version ()**

Returns the version of the current kernel API.

**Returns:**

The versionnumber of the kernel API

#### 4.1.2.10 `xid_t vc_getfilecontext (char const *filename)`

Returns the context of *filename*.

This function calls `vc_get_iattr()` with appropriate arguments to determine the context of *filename*. In error-case or when no context is assigned, `VC_NOCTX` will be returned. To differ between both cases, `errno` must be examined.

**WARNING:** this function can modify `errno` although no error happened.

##### Parameters:

*filename* The file to check

##### Returns:

The assigned context, or `VC_NOCTX` when an error occurred or no such assignment exists. `errno` will be 0 in the latter case

#### 4.1.2.11 `xid_t vc_new_s_context (xid_t ctx, unsigned int remove_cap, unsigned int flags)`

Moves current process into a context.

Puts current process into context *ctx*, removes the capabilities given in *remove\_cap* and sets *flags*.

##### Parameters:

*ctx* The new context; special values for are

- `VC_SAMECTX` which means the current context (just for changing caps and flags)
- `VC_DYNAMIC_XID` which means the next free context; this value can be used by ordinary users also

*remove\_cap* The linux capabilities which will be **removed**.

*flags* Special flags which will be set.

##### Returns:

The new context-id, or `VC_NOCTX` on errors; `errno` will be set appropriately

See <http://vserver.13thfloor.at/Stuff/Logic.txt> for details

#### 4.1.2.12 `int vc_reset_minmax (xid_t xid)`

Resets the minimum and maximum observed values for all resources.

##### Parameters:

*xid* The id of the context

##### Returns:

0 on success, and -1 on errors.

**4.1.2.13** `int vc_rlimit_stat (xid_t xid, int resource, struct vc_rlimit_stat * stat)`

Returns the current stats of *resource*.

**Parameters:**

*xid* The id of the context

*resource* The resource which will be queried

*stat* The result which will be filled with the stats

**Returns:**

0 on success, and -1 on errors.

**4.1.2.14** `int vc_set_ipv4root (uint32_t bcast, size_t nb, struct vc_ip_mask_pair const * ips)`

Sets the ipv4root information.

**Precondition:**

$nb < \text{NB\_IPV4ROOT} \ \&\& \ ips \neq 0$

**4.1.2.15** `int vc_set_rlimit (xid_t xid, int resource, struct vc_rlimit const * lim)`

Sets the limits of *resource*.

**Parameters:**

*xid* The id of the context

*resource* The resource which will be queried

*lim* The new limits

**Returns:**

0 on success, and -1 on errors.

**4.1.2.16** `int vc_syscall (uint32_t cmd, xid_t xid, void * data)`

The generic vserver syscall.

This function executes the generic vserver syscall. It uses the correct syscallnumber (which may differ between the different architectures).

**Parameters:**

*cmd* the command to be executed

*xid* the xid on which the cmd shall be applied

*data* additional arguments; depends on *cmd*

**Returns:**

depends on *cmd*; usually, -1 stands for an error



#### 4.1.2.17 int vc\_virt\_stat (xid\_t xid, struct vc\_virt\_stat \* stat)

Get more statistics about a context.

##### Parameters:

- xid* The context to get stats about
- stat* Where to store the result

##### Returns:

0 on success, -1 on errors.

## 4.2 Helper functions

### Data Structures

- struct [vc\\_err\\_listparser](#)  
*Information about parsing errors.*

### Functions

- size\_t [vc\\_get\\_nb\\_ipv4root](#) () VC\_ATTR\_CONST  
*Returns the value of NB\_IPV4ROOT.*
- bool [vc\\_parseLimit](#) (char const \*str, [vc\\_limit\\_t](#) \*res)  
*Parses a string describing a limit.*
- uint\_least64\_t [vc\\_text2bcap](#) (char const \*str, size\_t len)  
*Converts a single string into bcapability.*
- char const \* [vc\\_lobcap2text](#) (uint\_least64\_t \*val)  
*Converts the lowest bit of a bcapability or the entire value (when possible) to a textual representation.*
- int [vc\\_list2bcap](#) (char const \*str, size\_t len, struct [vc\\_err\\_listparser](#) \*err, struct [vc\\_ctx\\_caps](#) \*cap)  
*Converts a string into a bcapability-bitmask.*

#### 4.2.1 Detailed Description

Functions which are doing general helper tasks like parameter parsing.

#### 4.2.2 Function Documentation

##### 4.2.2.1 size\_t vc\_get\_nb\_ipv4root ()

Returns the value of NB\_IPV4ROOT.

This function returns the value of NB\_IPV4ROOT which was used when the library was built, but **not** the value which is used by the currently running kernel.

#### 4.2.2.2 int vc\_list2bcap (char const \* *str*, size\_t *len*, struct vc\_err\_listparser \* *err*, struct vc\_ctx\_caps \* *cap*)

Converts a string into a bcapability-bitmask.

Syntax of *str*:

```
LIST    <- ELEM | ELEM ' , ' LIST
ELEM    <- '~' ELEM | MASK | NAME
MASK    <- NUMBER | '^' NUMBER
NUMBER  <- 0[0-7]* | [1-9][0-9]* | 0x[0-9,a-f]+
NAME    <- <literal name> | "all" | "any" | "none"
```

When the '~' prefix is used, the bits will be unset and a '~' after another '~' will cancel both ones. The '^' prefix specifies a bitnumber instead of a bitmask.

"literal name" is everything which will be accepted by the [vc\\_text2bcap\(\)](#) function. The special values for NAME will be recognized case insensitively

##### Parameters:

- str* The string to be parsed
- len* The length of the string, or 0 for automatic detection
- err* Pointer to a structure for error-information, or NULL.
- cap* Pointer to a [vc\\_ctx\\_caps](#) structure holding the results; only the *bcaps* and *bmask* fields will be changed and already set values will not be honored. When an error occurred, *cap* will have the value of all processed valid BCAP parts.

##### Returns:

0 on success, -1 on error. In error case, *err* will hold position and length of the first not understood BCAP part

##### Precondition:

*str* != 0 && *cap* != 0; *cap*->*bcaps* and *cap*->*bmask* must be initialized

#### 4.2.2.3 char const\* vc\_lobcap2text (uint\_least64\_t \* *val*)

Converts the lowest bit of a bcapability or the entire value (when possible) to a textual representation.

##### Parameters:

- val* The string to be converted; on success, the detected bit(s) will be unset, in errorcase only the lowest set bit

##### Returns:

A textual representation of *val* resp. of its lowest set bit; or NULL in errorcase.

##### Precondition:

*val* != 0

##### Postcondition:

```
*valold != 0 <-> *valold > *valnew
*valold == 0 --> result == 0
```

#### 4.2.2.4 bool vc\_parseLimit (char const \* *str*, vc\_limit\_t \* *res*)

Parses a string describing a limit.

This function parses *str* and interprets special words like "inf" or suffixes. Valid suffixes are

- k ... 1000
- m ... 1000000
- K ... 1024
- M ... 1048576

##### Parameters:

*str* The string which shall be parsed

*res* Will be filled with the interpreted value; in errorcase, this value is undefined.

##### Returns:

*true*, iff the string *str* could be parsed. *res* will be filled with the interpreted value in this case.

##### Precondition:

*str*!=0 && *res*!=0

#### 4.2.2.5 uint\_least64\_t vc\_text2bcap (char const \* *str*, size\_t *len*)

Converts a single string into bcapability.

##### Parameters:

*str* The string to be parsed; both "CAP\_XXX" and "XXX" will be accepted

*len* The length of the string, or 0 for automatic detection

##### Returns:

0 on error; a bitmask on success

##### Precondition:

*str* != 0

## 5 util-vserver (libvserver) Data Structure Documentation

### 5.1 Mapping\_uint32 Struct Reference

#### Data Fields

- char const \*const *id*
- size\_t *len*
- uint\_least32\_t *val*

### 5.1.1 Detailed Description

Definition at line 62 of file internal.h.

The documentation for this struct was generated from the following file:

- [internal.h](#)

## 5.2 Mapping\_uint64 Struct Reference

### Data Fields

- char const \*const [id](#)
- size\_t [len](#)
- uint\_least64\_t [val](#)

### 5.2.1 Detailed Description

Definition at line 68 of file internal.h.

The documentation for this struct was generated from the following file:

- [internal.h](#)

## 5.3 vc\_ctx\_caps Struct Reference

Capabilities of process-contexts.

```
#include <vserver.h>
```

### Data Fields

- uint\_least64\_t [bcaps](#)  
*Mask of set common system capabilities.*
- uint\_least64\_t [bmask](#)  
*Mask of set and unset common system capabilities when used by set operations, or the modifiable capabilities when used by get operations.*
- uint\_least64\_t [ccaps](#)  
*Mask of set process context capabilities.*
- uint\_least64\_t [cmask](#)  
*Mask of set and unset process context capabilities when used by set operations, or the modifiable capabilities when used by get operations.*

### 5.3.1 Detailed Description

Capabilities of process-contexts.

Definition at line 646 of file `vserver.h`.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 5.4 `vc_ctx_dlimit` Struct Reference

### Data Fields

- `uint_least32_t` [space\\_used](#)
- `uint_least32_t` [space\\_total](#)
- `uint_least32_t` [inodes\\_used](#)
- `uint_least32_t` [inodes\\_total](#)
- `uint_least32_t` [reserved](#)

### 5.4.1 Detailed Description

Definition at line 823 of file `vserver.h`.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 5.5 `vc_ctx_flags` Struct Reference

Flags of process-contexts.

```
#include <vserver.h>
```

### Data Fields

- `uint_least64_t` [flagword](#)  
*Mask of set context flags.*
- `uint_least64_t` [mask](#)  
*Mask of set and unset context flags when used by set operations, or modifiable flags when used by get operations.*

### 5.5.1 Detailed Description

Flags of process-contexts.

Definition at line 636 of file `vserver.h`.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 5.6 vc\_ctx\_stat Struct Reference

Statistics about a context.

```
#include <vserver.h>
```

### Data Fields

- `uint_least32_t usecnt`  
*number of uses*
- `uint_least32_t tasks`  
*number of tasks*

#### 5.6.1 Detailed Description

Statistics about a context.

Definition at line 381 of file `vserver.h`.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 5.7 vc\_err\_listparser Struct Reference

Information about parsing errors.

```
#include <vserver.h>
```

### Data Fields

- `char const * ptr`  
*Pointer to the first character of an erroneous string.*
- `size_t len`  
*Length of the erroneous string.*

#### 5.7.1 Detailed Description

Information about parsing errors.

Definition at line 664 of file `vserver.h`.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 5.8 `vc_ip_mask_pair` Struct Reference

### Data Fields

- `uint32_t ip`
- `uint32_t mask`

### 5.8.1 Detailed Description

Definition at line 296 of file `vserver.h`.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 5.9 `vc_net_caps` Struct Reference

### Data Fields

- `uint_least64_t ncaps`
- `uint_least64_t cmask`

### 5.9.1 Detailed Description

Definition at line 556 of file `vserver.h`.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 5.10 `vc_net_flags` Struct Reference

### Data Fields

- `uint_least64_t flagword`
- `uint_least64_t mask`

### 5.10.1 Detailed Description

Definition at line 547 of file `vserver.h`.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 5.11 `vc_net_nx` Struct Reference

### Data Fields

- `vc_net_nx_type type`

- [size\\_t count](#)
- [uint32\\_t ip](#) [4]
- [uint32\\_t mask](#) [4]

### 5.11.1 Detailed Description

Definition at line 534 of file `vserver.h`.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 5.12 `vc_nx_info` Struct Reference

### Data Fields

- [nid\\_t nid](#)

### 5.12.1 Detailed Description

Definition at line 523 of file `vserver.h`.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 5.13 `vc_rlimit` Struct Reference

The limits of a resources.

```
#include <vserver.h>
```

### Data Fields

- [vc\\_limit\\_t min](#)  
*the guaranted minimum of a resources*
- [vc\\_limit\\_t soft](#)  
*the softlimit of a resource*
- [vc\\_limit\\_t hard](#)  
*the absolute hardlimit of a resource*

### 5.13.1 Detailed Description

The limits of a resources.

This is a triple consisting of a minimum, soft and hardlimit.

Definition at line 432 of file `vserver.h`.

The documentation for this struct was generated from the following file:



- [vserver.h](#)

## 5.14 `vc_rlimit_mask` Struct Reference

Masks describing the supported limits.

```
#include <vserver.h>
```

### Data Fields

- `uint_least32_t` [min](#)  
*masks the resources supporting a minimum limit*
- `uint_least32_t` [soft](#)  
*masks the resources supporting a soft limit*
- `uint_least32_t` [hard](#)  
*masks the resources supporting a hard limit*

### 5.14.1 Detailed Description

Masks describing the supported limits.

Definition at line 439 of file `vserver.h`.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 5.15 `vc_rlimit_stat` Struct Reference

Statistics for a resource limit.

```
#include <vserver.h>
```

### Data Fields

- `uint_least32_t` [hits](#)  
*number of hits on the limit*
- `uint_least64_t` [value](#)  
*current value*
- `uint_least64_t` [minimum](#)  
*minimum value observed*
- `uint_least64_t` [maximum](#)  
*maximum value observed*

### 5.15.1 Detailed Description

Statistics for a resource limit.

Definition at line 446 of file vserver.h.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 5.16 vc\_set\_sched Struct Reference

### Data Fields

- [uint\\_least32\\_t set\\_mask](#)
- [int\\_least32\\_t fill\\_rate](#)
- [int\\_least32\\_t interval](#)
- [int\\_least32\\_t fill\\_rate2](#)
- [int\\_least32\\_t interval2](#)
- [int\\_least32\\_t tokens](#)
- [int\\_least32\\_t tokens\\_min](#)
- [int\\_least32\\_t tokens\\_max](#)
- [int\\_least32\\_t priority\\_bias](#)
- [int\\_least32\\_t cpu\\_id](#)
- [int\\_least32\\_t bucket\\_id](#)

### 5.16.1 Detailed Description

Definition at line 806 of file vserver.h.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 5.17 vc\_virt\_stat Struct Reference

Contains further statistics about a context.

```
#include <vserver.h>
```

### Data Fields

- [uint\\_least64\\_t offset](#)
- [uint\\_least32\\_t uptime](#)
- [uint\\_least32\\_t nr\\_threads](#)
- [uint\\_least32\\_t nr\\_running](#)
- [uint\\_least32\\_t nr\\_uninterruptible](#)
- [uint\\_least32\\_t nr\\_onhold](#)
- [uint\\_least32\\_t nr\\_forks](#)
- [uint\\_least32\\_t load](#) [3]

### 5.17.1 Detailed Description

Contains further statistics about a context.

Definition at line 396 of file vserver.h.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 5.18 vc\_vx\_info Struct Reference

### Data Fields

- [xid\\_t](#) xid
- [pid\\_t](#) initpid

### 5.18.1 Detailed Description

Definition at line 600 of file vserver.h.

The documentation for this struct was generated from the following file:

- [vserver.h](#)

## 6 util-vserver (libvserver) File Documentation

### 6.1 internal.h File Reference

Declarations which are used by util-vserver internally.

```
#include "fmt.h"
```

```
#include "vserver.h"
```

```
#include <stdlib.h>
```

```
#include <stdbool.h>
```

Include dependency graph for internal.h:

## Data Structures

- struct [Mapping\\_uint32](#)
- struct [Mapping\\_uint64](#)

## Functions

- char \* **vc\_getVserverByCtx\_Internal** (xid\_t ctx, vcCfgStyle \*style, char const \*revdir, bool validate\_result)
- int **utilvserver\_checkCompatVersion** ()
- uint\_least32\_t **utilvserver\_checkCompatConfig** ()
- bool **utilvserver\_isDirectory** (char const \*path, bool follow\_link)
- bool **utilvserver\_isFile** (char const \*path, bool follow\_link)
- bool **utilvserver\_isLink** (char const \*path)
- int **utilvserver\_listparser\_uint32** (char const \*str, size\_t len, char const \*\*err\_ptr, size\_t \*err\_len, uint\_least32\_t \*flag, uint\_least32\_t \*mask, uint\_least32\_t(\*func)(char const \*, size\_t, bool \*)) NONNULL((1
- int **utilvserver\_listparser\_uint64** (char const \*str, size\_t len, char const \*\*err\_ptr, size\_t \*err\_len, uint\_least64\_t \*flag, uint\_least64\_t \*mask, uint\_least64\_t(\*func)(char const \*, size\_t, bool \*)) NONNULL((1
- ssize\_t **utilvserver\_value2text\_uint32** (char const \*str, size\_t len, struct [Mapping\\_uint32](#) const \*map, size\_t map\_len) NONNULL((1
- ssize\_t **utilvserver\_value2text\_uint64** (char const \*str, size\_t len, struct [Mapping\\_uint64](#) const \*map, size\_t map\_len) NONNULL((1
- ssize\_t **utilvserver\_text2value\_uint32** (uint\_least32\_t \*val, struct [Mapping\\_uint32](#) const \*map, size\_t map\_len) NONNULL((1
- ssize\_t **utilvserver\_text2value\_uint64** (uint\_least64\_t \*val, struct [Mapping\\_uint64](#) const \*map, size\_t map\_len) NONNULL((1

### 6.1.1 Detailed Description

Declarations which are used by util-vserver internally.

Definition in file [internal.h](#).

## 6.2 vserver.h File Reference

The public interface of the the libvserver library.

```
#include <stdint.h>
#include <stdlib.h>
#include <stdbool.h>
#include <sys/types.h>
#include <sched.h>
```

Include dependency graph for vserver.h:

This graph shows which files directly or indirectly include this file:

### Data Structures

- struct [vc\\_ip\\_mask\\_pair](#)
- struct [vc\\_ctx\\_stat](#)  
*Statistics about a context.*
- struct [vc\\_virt\\_stat](#)  
*Contains further statistics about a context.*
- struct [vc\\_rlimit](#)  
*The limits of a resources.*
- struct [vc\\_rlimit\\_mask](#)  
*Masks describing the supported limits.*
- struct [vc\\_rlimit\\_stat](#)  
*Statistics for a resource limit.*
- struct [vc\\_nx\\_info](#)
- struct [vc\\_net\\_nx](#)
- struct [vc\\_net\\_flags](#)
- struct [vc\\_net\\_caps](#)
- struct [vc\\_vx\\_info](#)
- struct [vc\\_ctx\\_flags](#)  
*Flags of process-contexts.*
- struct [vc\\_ctx\\_caps](#)  
*Capabilities of process-contexts.*
- struct [vc\\_err\\_listparser](#)  
*Information about parsing errors.*

- struct [vc\\_set\\_sched](#)
- struct [vc\\_ctx\\_dlimit](#)

## Defines

- #define [VC\\_NOCTX](#) ((xid\_t)(-1))
- #define [VC\\_NOXID](#) ((xid\_t)(-1))
- #define [VC\\_DYNAMIC\\_XID](#) ((xid\_t)(-1))
- #define [VC\\_SAMECTX](#) ((xid\_t)(-2))
- #define [VC\\_NONID](#) ((nid\_t)(-1))
- #define [VC\\_DYNAMIC\\_NID](#) ((nid\_t)(-1))
- #define [VC\\_LIM\\_INFINITY](#) (~0ULL)
- #define [VC\\_LIM\\_KEEP](#) (~1ULL)
- #define [VC\\_CDLIM\\_UNSET](#) (0U)
- #define [VC\\_CDLIM\\_INFINITY](#) (~0U)
- #define [VC\\_CDLIM\\_KEEP](#) (~1U)
- #define [S\\_CTX\\_INFO\\_LOCK](#) 1
- #define [S\\_CTX\\_INFO\\_SCHED](#) 2
- #define [S\\_CTX\\_INFO\\_NPROC](#) 4
- #define [S\\_CTX\\_INFO\\_PRIVATE](#) 8
- #define [S\\_CTX\\_INFO\\_INIT](#) 16
- #define [S\\_CTX\\_INFO\\_HIDEINFO](#) 32
- #define [S\\_CTX\\_INFO\\_ULIMIT](#) 64
- #define [S\\_CTX\\_INFO\\_NAMESPACE](#) 128
- #define [VC\\_CAP\\_CHOWN](#) 0
- #define [VC\\_CAP\\_DAC\\_OVERRIDE](#) 1
- #define [VC\\_CAP\\_DAC\\_READ\\_SEARCH](#) 2
- #define [VC\\_CAP\\_FOWNER](#) 3
- #define [VC\\_CAP\\_FSETID](#) 4
- #define [VC\\_CAP\\_KILL](#) 5
- #define [VC\\_CAP\\_SETGID](#) 6
- #define [VC\\_CAP\\_SETUID](#) 7
- #define [VC\\_CAP\\_SETPCAP](#) 8
- #define [VC\\_CAP\\_LINUX\\_IMMUTABLE](#) 9
- #define [VC\\_CAP\\_NET\\_BIND\\_SERVICE](#) 10
- #define [VC\\_CAP\\_NET\\_BROADCAST](#) 11
- #define [VC\\_CAP\\_NET\\_ADMIN](#) 12
- #define [VC\\_CAP\\_NET\\_RAW](#) 13
- #define [VC\\_CAP\\_IPC\\_LOCK](#) 14
- #define [VC\\_CAP\\_IPC\\_OWNER](#) 15
- #define [VC\\_CAP\\_SYS\\_MODULE](#) 16
- #define [VC\\_CAP\\_SYS\\_RAWIO](#) 17
- #define [VC\\_CAP\\_SYS\\_CHROOT](#) 18
- #define [VC\\_CAP\\_SYS\\_PTRACE](#) 19
- #define [VC\\_CAP\\_SYS\\_PACCT](#) 20
- #define [VC\\_CAP\\_SYS\\_ADMIN](#) 21
- #define [VC\\_CAP\\_SYS\\_BOOT](#) 22
- #define [VC\\_CAP\\_SYS\\_NICE](#) 23
- #define [VC\\_CAP\\_SYS\\_RESOURCE](#) 24

- #define [VC\\_CAP\\_SYS\\_TIME](#) 25
- #define [VC\\_CAP\\_SYS\\_TTY\\_CONFIG](#) 26
- #define [VC\\_CAP\\_MKNOD](#) 27
- #define [VC\\_CAP\\_LEASE](#) 28
- #define [VC\\_CAP\\_AUDIT\\_WRITE](#) 29
- #define [VC\\_CAP\\_AUDIT\\_CONTROL](#) 30
- #define [VC\\_IMMUTABLE\\_FILE\\_FL](#) 0x0000010lu
- #define [VC\\_IMMUTABLE\\_LINK\\_FL](#) 0x0008000lu
- #define [VC\\_IMMUTABLE\\_ALL](#) (VC\_IMMUTABLE\_LINK\_FL|VC\_IMMUTABLE\_FILE\_FL)
- #define [VC\\_IATTR\\_XID](#) 0x01000000u
- #define [VC\\_IATTR\\_ADMIN](#) 0x00000001u
- #define [VC\\_IATTR\\_WATCH](#) 0x00000002u
- #define [VC\\_IATTR\\_HIDE](#) 0x00000004u
- #define [VC\\_IATTR\\_FLAGS](#) 0x00000007u
- #define [VC\\_IATTR\\_BARRIER](#) 0x00010000u
- #define [VC\\_IATTR\\_IUNLINK](#) 0x00020000u
- #define [VC\\_IATTR\\_IMMUTABLE](#) 0x00040000u
- #define [VC\\_VXF\\_INFO\\_LOCK](#) 0x00000001ull
- #define [VC\\_VXF\\_INFO\\_NPROC](#) 0x00000004ull
- #define [VC\\_VXF\\_INFO\\_PRIVATE](#) 0x00000008ull
- #define [VC\\_VXF\\_INFO\\_INIT](#) 0x00000010ull
- #define [VC\\_VXF\\_INFO\\_HIDEINFO](#) 0x00000020ull
- #define [VC\\_VXF\\_INFO\\_ULIMIT](#) 0x00000040ull
- #define [VC\\_VXF\\_INFO\\_NAMESPACE](#) 0x00000080ull
- #define [VC\\_VXF\\_SCHED\\_HARD](#) 0x00000100ull
- #define [VC\\_VXF\\_SCHED\\_PRIO](#) 0x00000200ull
- #define [VC\\_VXF\\_SCHED\\_PAUSE](#) 0x00000400ull
- #define [VC\\_VXF\\_VIRT\\_MEM](#) 0x00010000ull
- #define [VC\\_VXF\\_VIRT\\_UPTIME](#) 0x00020000ull
- #define [VC\\_VXF\\_VIRT\\_CPU](#) 0x00040000ull
- #define [VC\\_VXF\\_VIRT\\_LOAD](#) 0x00080000ull
- #define [VC\\_VXF\\_VIRT\\_TIME](#) 0x00100000ull
- #define [VC\\_VXF\\_HIDE\\_MOUNT](#) 0x01000000ull
- #define [VC\\_VXF\\_HIDE\\_NETIF](#) 0x02000000ull
- #define [VC\\_VXF\\_HIDE\\_VINFO](#) 0x04000000ull
- #define [VC\\_VXF\\_STATE\\_SETUP](#) (1ULL<<32)
- #define [VC\\_VXF\\_STATE\\_INIT](#) (1ULL<<33)
- #define [VC\\_VXF\\_STATE\\_ADMIN](#) (1ULL<<34)
- #define [VC\\_VXF\\_SC\\_HELPER](#) (1ULL<<36)
- #define [VC\\_VXF\\_REBOOT\\_KILL](#) (1ULL<<37)
- #define [VC\\_VXF\\_PERSISTENT](#) (1ULL<<38)
- #define [VC\\_VXF\\_FORK\\_RSS](#) (1ULL<<48)
- #define [VC\\_VXF\\_PROLIFIC](#) (1ULL<<49)
- #define [VC\\_VXF\\_IGNEG\\_NICE](#) (1ULL<<52)
- #define [VC\\_VXC\\_SET\\_UTSNAME](#) 0x00000001ull
- #define [VC\\_VXC\\_SET\\_RLIMIT](#) 0x00000002ull
- #define [VC\\_VXC\\_RAW\\_ICMP](#) 0x00000100ull
- #define [VC\\_VXC\\_SYSLOG](#) 0x00001000ull
- #define [VC\\_VXC\\_SECURE\\_MOUNT](#) 0x00010000ull
- #define [VC\\_VXC\\_SECURE\\_REMOUNT](#) 0x00020000ull

- #define `VC_VXC_BINARY_MOUNT` 0x00040000ull
- #define `VC_VXC_QUOTA_CTL` 0x00100000ull
- #define `VC_VXC_ADMIN_MAPPER` 0x00200000ull
- #define `VC_VXC_ADMIN_CLOOP` 0x00400000ull
- #define `VC_VXSM_FILL_RATE` 0x0001
- #define `VC_VXSM_INTERVAL` 0x0002
- #define `VC_VXSM_FILL_RATE2` 0x0004
- #define `VC_VXSM_INTERVAL2` 0x0008
- #define `VC_VXSM_TOKENS` 0x0010
- #define `VC_VXSM_TOKENS_MIN` 0x0020
- #define `VC_VXSM_TOKENS_MAX` 0x0040
- #define `VC_VXSM_PRIO_BIAS` 0x0100
- #define `VC_VXSM_CPU_ID` 0x1000
- #define `VC_VXSM_BUCKET_ID` 0x2000
- #define `VC_VXSM_IDLE_TIME` 0x0200
- #define `VC_VXSM_FORCE` 0x0400
- #define `VC_VXSM_V3_MASK` 0x0173
- #define `VC_NXF_INFO_LOCK` 0x00000001ull
- #define `VC_NXF_INFO_PRIVATE` 0x00000008ull
- #define `VC_NXF_SINGLE_IP` 0x00000100ull
- #define `VC_NXF_HIDE_NETIF` 0x02000000ull
- #define `VC_NXF_STATE_SETUP` (1ULL<<32)
- #define `VC_NXF_STATE_ADMIN` (1ULL<<34)
- #define `VC_NXF_SC_HELPER` (1ULL<<36)
- #define `VC_NXF_PERSISTENT` (1ULL<<38)
- #define `VC_VLIMIT_NSOCK` 16
- #define `VC_VLIMIT_OPENFD` 17
- #define `VC_VLIMIT_ANON` 18
- #define `VC_VLIMIT_SHMEM` 19
- #define `VC_VLIMIT_SEMARY` 20
- #define `VC_VLIMIT_NSEMS` 21
- #define `VC_VLIMIT_DENTRY` 22
- #define `VC_VLIMIT_MAPPED` 23
- #define `VC_VCI_NO_DYNAMIC` (1 << 0)
- #define `VC_VCI_SPACES` (1 << 10)
- #define `CLONE_NEWNS` 0x00020000
- #define `CLONE_NEWUTS` 0x04000000
- #define `CLONE_NEWIPC` 0x08000000
- #define `VC_BAD_PERSONALITY` ((uint\_least32\_t)(-1))
- #define `VC_LIMIT_VSERVER_NAME_LEN` 1024
- #define `vcSKEL_INTERFACES` 1u
- #define `vcSKEL_PKGMGMT` 2u
- #define `vcSKEL_FILESYSTEM` 4u

## Typedefs

- typedef an\_unsigned\_integer\_type `xid_t`
- typedef an\_unsigned\_integer\_type `nid_t`
- typedef uint\_least64\_t `vc_limit_t`

*The type which is used for a single limit value.*



## Enumerations

- enum `vc_net_nx_type` {  
`vcNET_IPV4` = 1, `vcNET_IPV6` = 2, `vcNET_IPV4B` = 0x101, `vcNET_IPV6B` = 0x102,  
`vcNET_ANY` = ~0 }
- enum `vc_uts_type` {  
`vcVHI_CONTEXT`, `vcVHI_SYSNAME`, `vcVHI_NODENAME`, `vcVHI_RELEASE`,  
`vcVHI_VERSION`, `vcVHI_MACHINE`, `vcVHI_DOMAINNAME` }
- enum `vcFeatureSet` {  
`vcFEATURE_VKILL`, `vcFEATURE_IATTR`, `vcFEATURE_RLIMIT`, `vcFEATURE_COMPAT`,  
`vcFEATURE_MIGRATE`, `vcFEATURE_NAMESPACE`, `vcFEATURE_SCHED`, `vcFEATURE_V-`  
`INFO`,  
`vcFEATURE_VHI`, `vcFEATURE_VSHELPER0`, `vcFEATURE_VSHELPER`, `vcFEATURE_V-`  
`VWAIT`,  
`vcFEATURE_VNET` }
- enum `vcXidType` {  
`vcTYPE_INVALID`, `vcTYPE_MAIN`, `vcTYPE_WATCH`, `vcTYPE_STATIC`,  
`vcTYPE_DYNAMIC` }
- enum `vcCfgStyle` {  
`vcCFG_NONE`, `vcCFG_AUTO`, `vcCFG_LEGACY`, `vcCFG_RECENT_SHORT`,  
`vcCFG_RECENT_FULL` }

## Functions

- int `vc_syscall` (uint32\_t cmd, xid\_t xid, void \*data)  
*The generic vserver syscall.*
- int `vc_get_version` ()  
*Returns the version of the current kernel API.*
- int `vc_get_vci` ()  
*Returns the kernel configuration bits.*
- xid\_t `vc_new_s_context` (xid\_t ctx, unsigned int remove\_cap, unsigned int flags)  
*Moves current process into a context.*
- int `vc_set_ipv4root` (uint32\_t bcast, size\_t nb, struct `vc_ip_mask_pair` const \*ips)  
*Sets the ipv4root information.*
- size\_t `vc_get_nb_ipv4root` () VC\_ATTR\_CONST  
*Returns the value of NB\_IPV4ROOT.*
- xid\_t `vc_ctx_create` (xid\_t xid)  
*Creates a context without starting it.*
- int `vc_ctx_migrate` (xid\_t xid)  
*Moves the current process into the specified context.*

- `int vc_ctx_stat (xid_t xid, struct vc_ctx_stat *stat)`  
*Get some statistics about a context.*
- `int vc_virt_stat (xid_t xid, struct vc_virt_stat *stat)`  
*Get more statistics about a context.*
- `int vc_get_rlimit (xid_t xid, int resource, struct vc_rlimit *lim)`  
*Returns the limits of resource.*
- `int vc_set_rlimit (xid_t xid, int resource, struct vc_rlimit const *lim)`  
*Sets the limits of resource.*
- `int vc_get_rlimit_mask (xid_t xid, struct vc_rlimit_mask *lim)`
- `int vc_rlimit_stat (xid_t xid, int resource, struct vc_rlimit_stat *stat)`  
*Returns the current stats of resource.*
- `int vc_reset_minmax (xid_t xid)`  
*Resets the minimum and maximum observed values for all resources.*
- `bool vc_parseLimit (char const *str, vc_limit_t *res)`  
*Parses a string describing a limit.*
- `int vc_ctx_kill (xid_t ctx, pid_t pid, int sig)`  
*Sends a signal to a context/pid.*
- `nid_t vc_get_task_nid (pid_t pid)`
- `int vc_get_nx_info (nid_t nid, struct vc_nx_info *)`
- `nid_t vc_net_create (nid_t nid)`
- `int vc_net_migrate (nid_t nid)`
- `int vc_net_add (nid_t nid, struct vc_net_nx const *info)`
- `int vc_net_remove (nid_t nid, struct vc_net_nx const *info)`
- `int vc_get_nflags (nid_t, struct vc_net_flags *)`
- `int vc_set_nflags (nid_t, struct vc_net_flags const *)`
- `int vc_get_ncaps (nid_t, struct vc_net_caps *)`
- `int vc_set_ncaps (nid_t, struct vc_net_caps const *)`
- `int vc_set_iattr (char const *filename, xid_t xid, uint_least32_t flags, uint_least32_t mask)`
- `int vc_get_iattr (char const *filename, xid_t *xid, uint_least32_t *flags, uint_least32_t *mask)`  
*Returns information about attributes and assigned context of a file.*
- `xid_t vc_get_task_xid (pid_t pid)`  
*Returns the context of the given process.*
- `int vc_get_vx_info (xid_t xid, struct vc_vx_info *info)`
- `int vc_set_vhi_name (xid_t xid, vc_uts_type type, char const *val, size_t len)`
- `int vc_get_vhi_name (xid_t xid, vc_uts_type type, char *val, size_t len)`
- `bool vc_is_dynamic_xid (xid_t xid)`
- `int vc_enter_namespace (xid_t xid, uint_least64_t mask)`
- `int vc_set_namespace (xid_t xid, uint_least64_t mask)`
- `int vc_cleanup_namespace ()`

- `uint_least64_t vc_get_space_mask ()`
- `int vc_get_cflags (xid_t xid, struct vc_ctx_flags *)`
- `int vc_set_cflags (xid_t xid, struct vc_ctx_flags const *)`
- `int vc_get_ccaps (xid_t xid, struct vc_ctx_caps *)`
- `int vc_set_ccaps (xid_t xid, struct vc_ctx_caps const *)`
- `uint_least64_t vc_text2bcap (char const *str, size_t len)`  
*Converts a single string into bcapability.*
- `char const * vc_lobcap2text (uint_least64_t *val)`  
*Converts the lowest bit of a bcapability or the entire value (when possible) to a textual representation.*
- `int vc_list2bcap (char const *str, size_t len, struct vc_err_listparser *err, struct vc_ctx_caps *cap)`  
*Converts a string into a bcapability-bitmask.*
- `uint_least64_t vc_text2ccap (char const *, size_t len)`
- `char const * vc_loccap2text (uint_least64_t *)`
- `int vc_list2ccap (char const *, size_t len, struct vc_err_listparser *err, struct vc_ctx_caps *)`
- `int vc_list2cflag (char const *, size_t len, struct vc_err_listparser *err, struct vc_ctx_flags *flags)`
- `uint_least64_t vc_text2cflag (char const *, size_t len)`
- `char const * vc_locflag2text (uint_least64_t *)`
- `uint_least32_t vc_list2cflag_compat (char const *, size_t len, struct vc_err_listparser *err)`
- `uint_least32_t vc_text2cflag_compat (char const *, size_t len)`
- `char const * vc_hicflag2text_compat (uint_least32_t)`
- `int vc_text2cap (char const *)`
- `char const * vc_cap2text (unsigned int)`
- `int vc_list2nflag (char const *, size_t len, struct vc_err_listparser *err, struct vc_net_flags *flags)`
- `uint_least64_t vc_text2nflag (char const *, size_t len)`
- `char const * vc_lonflag2text (uint_least64_t *)`
- `uint_least64_t vc_text2ncap (char const *, size_t len)`
- `char const * vc_loncap2text (uint_least64_t *)`
- `int vc_list2ncap (char const *, size_t len, struct vc_err_listparser *err, struct vc_net_caps *)`
- `uint_least64_t vc_get_insecurebcaps () VC_ATTR_CONST`
- `uint_least32_t vc_text2personalityflag (char const *str, size_t len)`
- `char const * vc_lopersonality2text (uint_least32_t *)`
- `int vc_list2personalityflag (char const *, size_t len, uint_least32_t *personality, struct vc_err_listparser *err)`
- `uint_least32_t vc_str2personalitytype (char const *, size_t len)`
- `xid_t vc_getfilecontext (char const *filename)`  
*Returns the context of filename.*
- `int vc_set_sched (xid_t xid, struct vc_set_sched const *)`
- `int vc_add_dlimit (char const *filename, xid_t xid, uint_least32_t flags)`
- `int vc_rem_dlimit (char const *filename, xid_t xid, uint_least32_t flags)`
- `int vc_set_dlimit (char const *filename, xid_t xid, uint_least32_t flags, struct vc_ctx_dlimit const *limits)`
- `int vc_get_dlimit (char const *filename, xid_t xid, uint_least32_t flags, struct vc_ctx_dlimit *limits)`
- `int vc_wait_exit (xid_t xid)`  
*Waits for the end of a context.*
- `bool vc_isSupported (vcFeatureSet) VC_ATTR_CONST`

- `bool vc_isSupportedString` (char const \*)
- `vcXidType vc_getXIDType` (xid\_t xid) VC\_ATTR\_CONST
- `xid_t vc_xidopt2xid` (char const \*, bool honor\_static, char const \*\*err\_info)
- `nid_t vc_nidopt2nid` (char const \*, bool honor\_static, char const \*\*err\_info)
- `vcCfgStyle vc_getVserverCfgStyle` (char const \*id)
- `char * vc_getVserverName` (char const \*id, vcCfgStyle style)
- `char * vc_getVserverCfgDir` (char const \*id, vcCfgStyle style)
- `char * vc_getVserverAppDir` (char const \*id, vcCfgStyle style, char const \*app)
- `char * vc_getVserverVdir` (char const \*id, vcCfgStyle style, bool physical)
- `xid_t vc_getVserverCtx` (char const \*id, vcCfgStyle style, bool honor\_static, bool \*is\_running)
- `char * vc_getVserverByCtx` (xid\_t ctx, vcCfgStyle \*style, char const \*revdir)
- `int vc_compareVserverById` (char const \*lhs, vcCfgStyle lhs\_style, char const \*rhs, vcCfgStyle rhs\_style)
- `int vc_createSkeleton` (char const \*id, vcCfgStyle style, int flags)

### 6.2.1 Detailed Description

The public interface of the the libvserver library.

Definition in file [vserver.h](#).

### 6.2.2 Define Documentation

#### 6.2.2.1 #define VC\_DYNAMIC\_XID ((xid\_t)(-1))

the value which means a random (the next free) ctx

Definition at line 66 of file [vserver.h](#).

#### 6.2.2.2 #define VC\_NOCTX ((xid\_t)(-1))

the value which is returned in error-case (no ctx found)

Definition at line 63 of file [vserver.h](#).

#### 6.2.2.3 #define VC\_SAMECTX ((xid\_t)(-2))

the value which means the current ctx

Definition at line 68 of file [vserver.h](#).

### 6.2.3 Typedef Documentation

#### 6.2.3.1 typedef uint\_least64\_t vc\_limit\_t

The type which is used for a single limit value.

Special values are

- `VC_LIM_INFINITY` ... which is the infinite value
- `VC_LIM_KEEP` ... which is used to mark values which shall not be modified by the [vc\\_set\\_rlimit\(\)](#) operation.

Else, the interpretation of the value depends on the corresponding resource; it might be bytes, pages, seconds or litres of beer.

Definition at line 427 of file vserver.h.

#### 6.2.3.2 an\_unsigned\_integer\_type xid\_t

The identifier of a context.

Definition at line 288 of file vserver.h.

### 6.2.4 Enumeration Type Documentation

#### 6.2.4.1 enum vc\_net\_nx\_type

Enumerator:

*vcNET\_IPV4*  
*vcNET\_IPV6*  
*vcNET\_IPV4B*  
*vcNET\_IPV6B*  
*vcNET\_ANY*

Definition at line 530 of file vserver.h.

#### 6.2.4.2 enum vc\_uts\_type

Enumerator:

*vcVHI\_CONTEXT*  
*vcVHI\_SYSNAME*  
*vcVHI\_NODENAME*  
*vcVHI\_RELEASE*  
*vcVHI\_VERSION*  
*vcVHI\_MACHINE*  
*vcVHI\_DOMAINNAME*

Definition at line 616 of file vserver.h.

#### 6.2.4.3 enum vcCfgStyle

Enumerator:

*vcCFG\_NONE*  
*vcCFG\_AUTO*  
*vcCFG\_LEGACY*  
*vcCFG\_RECENT\_SHORT*  
*vcCFG\_RECENT\_FULL*

Definition at line 874 of file vserver.h.

#### 6.2.4.4 enum vcFeatureSet

Enumerator:

*vcFEATURE\_VKILL*  
*vcFEATURE\_IATTR*  
*vcFEATURE\_RLIMIT*  
*vcFEATURE\_COMPAT*  
*vcFEATURE\_MIGRATE*  
*vcFEATURE\_NAMESPACE*  
*vcFEATURE\_SCHED*  
*vcFEATURE\_VINFO*  
*vcFEATURE\_VHI*  
*vcFEATURE\_VSHELPER0*  
*vcFEATURE\_VSHELPER*  
*vcFEATURE\_VWAIT*  
*vcFEATURE\_VNET*

Definition at line 853 of file vserver.h.

#### 6.2.4.5 enum vcXidType

Enumerator:

*vcTYPE\_INVALID*  
*vcTYPE\_MAIN*  
*vcTYPE\_WATCH*  
*vcTYPE\_STATIC*  
*vcTYPE\_DYNAMIC*

Definition at line 864 of file vserver.h.

### 6.2.5 Function Documentation

#### 6.2.5.1 int vc\_add\_dlimit (char const \* *filename*, xid\_t *xid*, uint\_least32\_t *flags*)

Add a disk limit to a file system.

#### 6.2.5.2 int vc\_createSkeleton (char const \* *id*, vcCfgStyle *style*, int *flags*)

Create a basic configuration skeleton for a vserver plus toplevel directories for pkgmanagment and filesystem (when requested).

#### 6.2.5.3 int vc\_get\_dlimit (char const \* *filename*, xid\_t *xid*, uint\_least32\_t *flags*, struct vc\_ctx\_dlimit \* *limits*)

Get a disk limit.

**6.2.5.4 char\* vc\_getVserverAppDir (char const \* *id*, vcCfgStyle *style*, char const \* *app*)**

Returns the path of the configuration directory for the given application. The result will be allocated and must be freed by the caller.

**6.2.5.5 char\* vc\_getVserverByCtx (xid\_t *ctx*, vcCfgStyle \* *style*, char const \* *revdir*)**

Resolves the cfg-path of the vserver owning the given ctx. 'revdir' will be used as the directory holding the mapping-links; when NULL, the default value will be assumed. The result will be allocated and must be freed by the caller.

**6.2.5.6 char\* vc\_getVserverCfgDir (char const \* *id*, vcCfgStyle *style*)**

Returns the path of the vserver configuration directory. When the given vserver does not exist, or when it does not have such a directory, NULL will be returned. Else, the result will be allocated and must be freed by the caller.

**6.2.5.7 xid\_t vc\_getVserverCtx (char const \* *id*, vcCfgStyle *style*, bool *honor\_static*, bool \* *is\_running*)**

Returns the ctx of the given vserver. When vserver is not running and 'honor\_static' is false, VC\_NOCTX will be returned. Else, when 'honor\_static' is true and a static assignment exists, those value will be returned. Else, the result will be VC\_NOCTX.

When 'is\_running' is not null, the status of the vserver will be assigned to this variable.

**6.2.5.8 char\* vc\_getVserverName (char const \* *id*, vcCfgStyle *style*)**

Resolves the name of the vserver. The result will be allocated and must be freed by the caller.

**6.2.5.9 char\* vc\_getVserverVdir (char const \* *id*, vcCfgStyle *style*, bool *physical*)**

Returns the path to the vserver root-directory. The result will be allocated and must be freed by the caller.

**6.2.5.10 bool vc\_is\_dynamic\_xid (xid\_t *xid*)**

Returns true iff *xid* is a dynamic xid

**6.2.5.11 nid\_t vc\_nidopt2nid (char const \*, bool *honor\_static*, char const \*\* *err\_info*)**

Maps a nid given at '-nid' options to a nid\_t

**6.2.5.12 int vc\_rem\_dlimit (char const \* *filename*, xid\_t *xid*, uint\_least32\_t *flags*)**

Remove a disk limit from a file system.

**6.2.5.13 int vc\_set\_dlimit (char const \* *filename*, xid\_t *xid*, uint\_least32\_t *flags*, struct vc\_ctx\_dlimit const \* *limits*)**

Set a disk limit.

**6.2.5.14** `xid_t vc_xidopt2xid (char const *, bool honor_static, char const ** err_info)`

Maps an xid given at '-xid' options to an xid\_t



## Index

### helper

- [vc\\_get\\_nb\\_ipv4root](#), 8
- [vc\\_list2bcap](#), 8
- [vc\\_lobcap2text](#), 9
- [vc\\_parseLimit](#), 9
- [vc\\_text2bcap](#), 10

Helper functions, 8

[internal.h](#), 18

[Mapping\\_uint32](#), 10

[Mapping\\_uint64](#), 11

[Syscall wrappers](#), 2

### syscalls

- [vc\\_ctx\\_create](#), 3
- [vc\\_ctx\\_kill](#), 3
- [vc\\_ctx\\_migrate](#), 3
- [vc\\_ctx\\_stat](#), 4
- [vc\\_get\\_iattr](#), 4
- [vc\\_get\\_rlimit](#), 4
- [vc\\_get\\_task\\_xid](#), 5
- [vc\\_get\\_vci](#), 5
- [vc\\_get\\_version](#), 5
- [vc\\_getfilecontext](#), 5
- [vc\\_new\\_s\\_context](#), 6
- [vc\\_reset\\_minmax](#), 6
- [vc\\_rlimit\\_stat](#), 6
- [vc\\_set\\_ipv4root](#), 6
- [vc\\_set\\_rlimit](#), 7
- [vc\\_syscall](#), 7
- [vc\\_virt\\_stat](#), 7

[vc\\_add\\_dlimit](#)  
[vserver.h](#), 29

[vc\\_createSkeleton](#)  
[vserver.h](#), 29

[vc\\_ctx\\_caps](#), 11

[vc\\_ctx\\_create](#)  
[syscalls](#), 3

[vc\\_ctx\\_dlimit](#), 12

[vc\\_ctx\\_flags](#), 12

[vc\\_ctx\\_kill](#)  
[syscalls](#), 3

[vc\\_ctx\\_migrate](#)  
[syscalls](#), 3

[vc\\_ctx\\_stat](#), 12  
[syscalls](#), 4

[VC\\_DYNAMIC\\_XID](#)  
[vserver.h](#), 27

[vc\\_err\\_listparser](#), 13

[vc\\_get\\_dlimit](#)  
[vserver.h](#), 29

[vc\\_get\\_iattr](#)  
[syscalls](#), 4

[vc\\_get\\_nb\\_ipv4root](#)  
[helper](#), 8

[vc\\_get\\_rlimit](#)  
[syscalls](#), 4

[vc\\_get\\_task\\_xid](#)  
[syscalls](#), 5

[vc\\_get\\_vci](#)  
[syscalls](#), 5

[vc\\_get\\_version](#)  
[syscalls](#), 5

[vc\\_getfilecontext](#)  
[syscalls](#), 5

[vc\\_getVserverAppDir](#)  
[vserver.h](#), 29

[vc\\_getVserverByCtx](#)  
[vserver.h](#), 30

[vc\\_getVserverCfgDir](#)  
[vserver.h](#), 30

[vc\\_getVserverCtx](#)  
[vserver.h](#), 30

[vc\\_getVserverName](#)  
[vserver.h](#), 30

[vc\\_getVserverVdir](#)  
[vserver.h](#), 30

[vc\\_ip\\_mask\\_pair](#), 13

[vc\\_is\\_dynamic\\_xid](#)  
[vserver.h](#), 30

[vc\\_limit\\_t](#)  
[vserver.h](#), 27

[vc\\_list2bcap](#)  
[helper](#), 8

[vc\\_lobcap2text](#)  
[helper](#), 9

[vc\\_net\\_caps](#), 14

[vc\\_net\\_flags](#), 14

[vc\\_net\\_nx](#), 14

[vc\\_net\\_nx\\_type](#)  
[vserver.h](#), 28

[vc\\_new\\_s\\_context](#)  
[syscalls](#), 6

[vc\\_nidopt2nid](#)  
[vserver.h](#), 30

[VC\\_NOCTX](#)  
[vserver.h](#), 27

[vc\\_nx\\_info](#), 15

[vc\\_parseLimit](#)

- helper, 9
- vc\_rem\_dlimit
  - vserver.h, 30
- vc\_reset\_minmax
  - syscalls, 6
- vc\_rlimit, 15
- vc\_rlimit\_mask, 16
- vc\_rlimit\_stat, 16
  - syscalls, 6
- VC\_SAMECTX
  - vserver.h, 27
- vc\_set\_dlimit
  - vserver.h, 30
- vc\_set\_ipv4root
  - syscalls, 6
- vc\_set\_rlimit
  - syscalls, 7
- vc\_set\_sched, 17
- vc\_syscall
  - syscalls, 7
- vc\_text2bcap
  - helper, 10
- vc\_uts\_type
  - vserver.h, 28
- vc\_virt\_stat, 17
  - syscalls, 7
- vc\_vx\_info, 18
- vc\_xidopt2xid
  - vserver.h, 30
- vcCFG\_AUTO
  - vserver.h, 28
- vcCFG\_LEGACY
  - vserver.h, 28
- vcCFG\_NONE
  - vserver.h, 28
- vcCFG\_RECENT\_FULL
  - vserver.h, 28
- vcCFG\_RECENT\_SHORT
  - vserver.h, 28
- vcCfgStyle
  - vserver.h, 28
- vcFEATURE\_COMPAT
  - vserver.h, 29
- vcFEATURE\_IATTR
  - vserver.h, 29
- vcFEATURE\_MIGRATE
  - vserver.h, 29
- vcFEATURE\_NAMESPACE
  - vserver.h, 29
- vcFEATURE\_RLIMIT
  - vserver.h, 29
- vcFEATURE\_SCHED
  - vserver.h, 29
- vcFEATURE\_VHI
  - vserver.h, 29
- vcFEATURE\_VINFO
  - vserver.h, 29
- vcFEATURE\_VKILL
  - vserver.h, 29
- vcFEATURE\_VNET
  - vserver.h, 29
- vcFEATURE\_VSHELPER
  - vserver.h, 29
- vcFEATURE\_VSHELPER0
  - vserver.h, 29
- vcFEATURE\_VWAIT
  - vserver.h, 29
- vcFeatureSet
  - vserver.h, 28
- vcNET\_ANY
  - vserver.h, 28
- vcNET\_IPV4
  - vserver.h, 28
- vcNET\_IPV4B
  - vserver.h, 28
- vcNET\_IPV6
  - vserver.h, 28
- vcNET\_IPV6B
  - vserver.h, 28
- vcTYPE\_DYNAMIC
  - vserver.h, 29
- vcTYPE\_INVALID
  - vserver.h, 29
- vcTYPE\_MAIN
  - vserver.h, 29
- vcTYPE\_STATIC
  - vserver.h, 29
- vcTYPE\_WATCH
  - vserver.h, 29
- vcVHI\_CONTEXT
  - vserver.h, 28
- vcVHI\_DOMAINNAME
  - vserver.h, 28
- vcVHI\_MACHINE
  - vserver.h, 28
- vcVHI\_NODENAME
  - vserver.h, 28
- vcVHI\_RELEASE
  - vserver.h, 28
- vcVHI\_SYSNAME
  - vserver.h, 28
- vcVHI\_VERSION
  - vserver.h, 28
- vcXidType
  - vserver.h, 29
- vserver.h, 19
  - vc\_add\_dlimit, 29
  - vc\_createSkeleton, 29

VC\_DYNAMIC\_XID, 27  
vc\_get\_dlimit, 29  
vc\_getVserverAppDir, 29  
vc\_getVserverByCtx, 30  
vc\_getVserverCfgDir, 30  
vc\_getVserverCtx, 30  
vc\_getVserverName, 30  
vc\_getVserverVdir, 30  
vc\_is\_dynamic\_xid, 30  
vc\_limit\_t, 27  
vc\_net\_nx\_type, 28  
vc\_nidopt2nid, 30  
VC\_NOCTX, 27  
vc\_rem\_dlimit, 30  
VC\_SAMECTX, 27  
vc\_set\_dlimit, 30  
vc\_uts\_type, 28  
vc\_xidopt2xid, 30  
vcCFG\_AUTO, 28  
vcCFG\_LEGACY, 28  
vcCFG\_NONE, 28  
vcCFG\_RECENT\_FULL, 28  
vcCFG\_RECENT\_SHORT, 28  
vcCfgStyle, 28  
vcFEATURE\_COMPAT, 29  
vcFEATURE\_IATTR, 29  
vcFEATURE\_MIGRATE, 29  
vcFEATURE\_NAMESPACE, 29  
vcFEATURE\_RLIMIT, 29  
vcFEATURE\_SCHED, 29  
vcFEATURE\_VHI, 29  
vcFEATURE\_VINFO, 29  
vcFEATURE\_VKILL, 29  
vcFEATURE\_VNET, 29  
vcFEATURE\_VSHELPER, 29  
vcFEATURE\_VSHELPER0, 29  
vcFEATURE\_VWAIT, 29  
vcFeatureSet, 28  
vcNET\_ANY, 28  
vcNET\_IPV4, 28  
vcNET\_IPV4B, 28  
vcNET\_IPV6, 28  
vcNET\_IPV6B, 28  
vcTYPE\_DYNAMIC, 29  
vcTYPE\_INVALID, 29  
vcTYPE\_MAIN, 29  
vcTYPE\_STATIC, 29  
vcTYPE\_WATCH, 29  
vcVHI\_CONTEXT, 28  
vcVHI\_DOMAINNAME, 28  
vcVHI\_MACHINE, 28  
vcVHI\_NODENAME, 28  
vcVHI\_RELEASE, 28  
vcVHI\_SYSNAME, 28  
vcVHI\_VERSION, 28  
vcXidType, 29  
xid\_t, 28  
xid\_t  
vserver.h, 28